



Turn-Key Storage and Virtualization Server

45Drives offers tightly integrated storage and virtualization solutions that combine enterprise-grade hardware, open-source software, and comprehensive support. Our solutions give organizations complete control and flexibility over their data, eliminating risk associated with vendor lock-in. The Proxinator VM2 offers turn-key Proxmox Virtual Environment (VE) with integrated access to high speed storage.



HARDWARE

- 2 Bay NVMe Server
- Made in North America with 16g Steel
- 1U Rackmount Server (Rails Included)
- Up to 61.44 TB of Raw Storage Capacity
- Direct-Wire Architecture
- Tool-less & Caddieless Drive Access
- Latest Generation of AMD EPYC CPUs
- Up to 1.125TB DDR5 ECC Memory
- GPU-ready (single slot)
- Redundant Power Supply
- IPMI capable

SOFTWARE

- Preloaded with Proxmox VE
- Integrated with ZFS
- Single Pane UI for VMs and Storage
- Proxmox VE Cluster Ready
- File & Block Storage
- SMB, NFS, iSCSI Protocols
- Proxmox Backup Server Ready
- Native Veeam Backup Integration
- Administrative Training Available



THE PROXINATOR[™] By 45Drives

VM2



| | Base | Enhanced | Turbo |
|------------------------------|---|---|---|
| CPU (AMD 8004) | AMD EPYC 8124P 16 CORES, 2.45 GHz MAX BOOST 3 GHz | AMD EPYC 8224P 24 CORES, 2.55 GHz MAX BOOST 3 GHz | AMD EPYC 8324P 32 CORES, 2.65GHz MAX BOOST 3GHz |
| CPU Architecture | 64-bit | | |
| Maximum Memory | 1.125TB | | |
| Maximum RDIMM Capacity | 6-Channel DDR5 RDIMM up to 96GB supported | | |
| Total Memory Slots | 12 x DIMM slots | | |
| Motherboard Model | ME03-CE0 | | |
| PCI Slots (AMD) | 2 x PCIe Gen5 x 16 expansion slots (*Usable) *1x low-profile single-slot PCIe card and 1x full-height single-slot PCIe Card 1 x M.2 slot with PCIe Gen3 x 4 interface | | |
| Electrical | 100-240 VAC, 47-63 Hz IEC-320-C14 (server side) NEMA 5-15P (wall side) *Other regions also available | | |
| Backplane | Not Applicable | | |
| Number of Storage Drive Bays | 2 | | |
| Maximum Raw Capacity | 61.44TB (Using 30.72 TB 15mm U.3 NVMe SSDs) | | |
| ZFS RAID Options | 0, 1 | | |
| Networking (On-Board) | 2x 10 Gb/s | | |
| Networking (Add-Ons) | 10, 25, 40, and 100GbE | | |
| Power | 800W 1U Redundant PSU | | |
| Form Factor | 1U | | |
| HBA Card | None | | |
| Operating System | Proxmox Virtual Environment | | |
| Boot Drives | 2 x 480GB Enterprise SATA SSDs (Mirrored) | | |
| Expansion | Ceph Cluster-Ready | | |
| Dimensions | 19.76 "L x 19 " W x 1.7500"H | | |